# PowerMOS transistor — BUK454-800A/B

## GENERAL DESCRIPTION

N-channel enhancement mode field-effect power transistor in a plastic envelope.
The device is intended for use in Switched Mode Power Supplies (SMPS), motor control, welding, DC/DC and AC/DC converters, and in general purpose switching applications.


## QUICK REFERENCE DATA

| SYMBOL | PARAMETER | MAX. | MAX. | UNIT |
|---|---|---|---|---|
| | BUK454 | -800A | -800B | |
| $V_{DS}$ | Drain-source voltage | 800 | 800 | V |
| $I_D$ | Drain current (DC) | 2.4 | 2.0 | A |
| $P_{tot}$ | Total power dissipation | 85 | 85 | W |
| $R_{DS(ON)}$ | Drain-source on-state resistance | 6 | 8 | Ω |


## PINNING - TO220AB

| PIN | DESCRIPTION |
|---|---|
| 1 | gate |
| 2 | drain |
| 3 | source |
| tab | drain |

## PIN CONFIGURATION




## SYMBOL




## LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134)

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | | UNIT |
|---|---|---|---|---|---|---|
| $V_{DS}$ | Drain-source voltage | - | - | 800 | | V |
| $V_{DGR}$ | Drain-gate voltage | $R_{GS}$ = 20 kΩ | - | 800 | | V |
| $\pm V_{GS}$ | Gate-source voltage | - | - | 30 | | V |
| | | | | -800A | -800B | |
| $I_D$ | Drain current (DC) | $T_{mb}$ = 25 ˚C | - | 2.4 | 2.0 | A |
| $I_D$ | Drain current (DC) | $T_{mb}$ = 100 ˚C | - | 1.5 | 1.25 | A |
| $I_{DM}$ | Drain current (pulse peak value) | $T_{mb}$ = 25 ˚C | - | 9.5 | 8 | A |
| $P_{tot}$ | Total power dissipation | $T_{mb}$ = 25 ˚C | - | 85 | | W |
| $T_{stg}$ | Storage temperature | - | - 55 | 150 | | ˚C |
| $T_j$ | Junction Temperature | - | - | 150 | | ˚C |

## THERMAL RESISTANCES

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|
| $R_{th\ j\text{-}mb}$ | Thermal resistance junction to mounting base | | - | - | 1.47 | K/W |
| $R_{th\ j\text{-}a}$ | Thermal resistance junction to ambient | | - | 60 | - | K/W |

## STATIC CHARACTERISTICS

$T_{mb}$ = 25 ˚C unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage | $V_{GS}$ = 0 V; $I_D$ = 0.25 mA | 800 | - | - | V |
| $V_{GS(TO)}$ | Gate threshold voltage | $V_{DS}$ = $V_{GS}$; $I_D$ = 1 mA | 2.1 | 3.0 | 4.0 | V |
| $I_{DSS}$ | Zero gate voltage drain current | $V_{DS}$ = 800 V; $V_{GS}$ = 0 V; $T_j$ = 25 ˚C | - | 2 | 20 | µA |
| $I_{DSS}$ | Zero gate voltage drain current | $V_{DS}$ = 800 V; $V_{GS}$ = 0 V; $T_j$ =125 ˚C | - | 0.1 | 1.0 | mA |
| $I_{GSS}$ | Gate source leakage current | $V_{GS}$ = ±30 V; $V_{DS}$ = 0 V | - | 10 | 100 | nA |
| $R_{DS(ON)}$ | Drain-source on-state resistance | $V_{GS}$ = 10 V; **BUK454-800A** | - | 5 | 6 | Ω |
| | | $I_D$ = 1.0 A **BUK454-800B** | - | 6 | 8 | Ω |

## DYNAMIC CHARACTERISTICS

$T_{mb}$ = 25 ˚C unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|
| $g_{fs}$ | Forward transconductance | $V_{DS}$ = 25 V; $I_D$ = 1.0 A | 1.0 | 2.3 | - | S |
| $C_{iss}$ | Input capacitance | $V_{GS}$ = 0 V; $V_{DS}$ = 25 V; f = 1 MHz | - | 450 | 750 | pF |
| $C_{oss}$ | Output capacitance | | - | 42 | 70 | pF |
| $C_{rss}$ | Feedback capacitance | | - | 15 | 30 | pF |
| $t_{d\,on}$ | Turn-on delay time | $V_{DD}$ = 30 V; $I_D$ = 1.9 A; | - | 15 | 20 | ns |
| $t_r$ | Turn-on rise time | $V_{GS}$ = 10 V; $R_{GS}$ = 50 Ω; | - | 25 | 40 | ns |
| $t_{d\,off}$ | Turn-off delay time | $R_{gen}$ = 50 Ω | - | 50 | 65 | ns |
| $t_f$ | Turn-off fall time | | - | 30 | 40 | ns |
| $L_d$ | Internal drain inductance | Measured from contact screw on tab to centre of die | - | 3.5 | - | nH |
| $L_d$ | Internal drain inductance | Measured from drain lead 6 mm from package to centre of die | - | 4.5 | - | nH |
| $L_s$ | Internal source inductance | Measured from source lead 6 mm from package to source bond pad | - | 7.5 | - | nH |

## REVERSE DIODE LIMITING VALUES AND CHARACTERISTICS

$T_{mb}$ = 25 ˚C unless otherwise specified

| SYMBOL | PARAMETER | CONDITIONS | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|
| $I_{DR}$ | Continuous reverse drain current | - | - | - | 2.6 | A |
| $I_{DRM}$ | Pulsed reverse drain current | - | - | - | 10 | A |
| $V_{SD}$ | Diode forward voltage | $I_F$ = 2.6 A ; $V_{GS}$ = 0 V | - | 1.0 | 1.3 | V |
| $t_{rr}$ | Reverse recovery time | $I_F$ = 2.6 A; -d$I_F$/dt = 100 A/µs; | - | 230 | - | ns |
| $Q_{rr}$ | Reverse recovery charge | $V_{GS}$ = 0 V; $V_R$ = 100 V | - | 1.9 | - | µC |





*Fig.1. Normalised power dissipation.*
*PD% = 100·$P_D$/$P_{D\ 25\ °C}$ = f($T_{mb}$)*





*Fig.4. Transient thermal impedance.*
*$Z_{th\ j\text{-}mb}$ = f(t); parameter D = $t_p$/T*





*Fig.2. Normalised continuous drain current.*
*ID% = 100·$I_D$/$I_{D\ 25\ °C}$ = f($T_{mb}$); conditions: $V_{GS}$ ≥ 10 V*





*Fig.5. Typical output characteristics, $T_j$ = 25 ˚C.*
*$I_D$ = f($V_{DS}$); parameter $V_{GS}$*





*Fig.3. Safe operating area. $T_{mb}$ = 25 ˚C*
*$I_D$ & $I_{DM}$ = f($V_{DS}$); $I_{DM}$ single pulse; parameter $t_p$*





*Fig.6. Typical on-state resistance, $T_j$ = 25 ˚C.*
*$R_{DS(ON)}$ = f($I_D$); parameter $V_{GS}$*





*Fig.7. Typical transfer characteristics.*
*$I_D = f(V_{GS})$ ; conditions: $V_{DS}$ = 25 V; parameter $T_j$*





*Fig.10. Gate threshold voltage.*
*$V_{GS(TO)} = f(T_j)$; conditions: $I_D$ = 1 mA; $V_{DS} = V_{GS}$*





*Fig.8. Typical transconductance, $T_j$ = 25 ˚C.*
*$g_{fs} = f(I_D)$; conditions: $V_{DS}$ = 25 V*





*Fig.11. Sub-threshold drain current.*
*$I_D = f(V_{GS})$; conditions: $T_j$ = 25 ˚C; $V_{DS} = V_{GS}$*





*Fig.9. Normalised drain-source on-state resistance.*
*$a = R_{DS(ON)}/R_{DS(ON)25\,°C} = f(T_j)$; $I_D$ = 1.0 A; $V_{GS}$ = 10 V*





*Fig.12. Typical capacitances, $C_{iss}$, $C_{oss}$, $C_{rss}$.*
*$C = f(V_{DS})$; conditions: $V_{GS}$ = 0 V; f = 1 MHz*





*Fig.13. Typical turn-on gate-charge characteristics. $V_{GS} = f(Q_G)$; conditions: $I_D = 2.4$ A; parameter $V_{DS}$*





*Fig.14. Typical reverse diode current. $I_F = f(V_{SDS})$; conditions: $V_{GS} = 0$ V; parameter $T_j$*

## MECHANICAL DATA

*Dimensions in mm*

*Net Mass: 2 g*





*Fig.15. TO220AB; pin 2 connected to mounting base.*

**Notes**

1. Observe the general handling precautions for electrostatic-discharge sensitive devices (ESDs) to prevent damage to MOS gate oxide.
2. Refer to mounting instructions for TO220 envelopes.
3. Epoxy meets UL94 V0 at 1/8".

## DEFINITIONS

| **Data sheet status** | |
|---|---|
| Objective specification | This data sheet contains target or goal specifications for product development. |
| Preliminary specification | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification | This data sheet contains final product specifications. |
| **Limiting values** | |
| Limiting values are given in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability. | |
| **Application information** | |
| Where application information is given, it is advisory and does not form part of the specification. | |
| © **Philips Electronics N.V. 1996** | |
| All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. | |
| The information presented in this document does not form part of any quotation or contract, it is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights. | |

## LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.